

# BoltaSoft® Marine Upholstery Headlining

## Product Specifications:

General	
Total Wt. – oz./sq. yd. (CFFA-700d)	14
Total Wt. – oz./lin. yd. (CFFA-700d)	22.0
Width (min.) – in. (CFFA-700a)	54"
Topskin Thickness	.009"
Face Content	PVC

Backing	
Construction	Woven
Content	100% Polyester
Fiber Type	Spun

Adhesion (CFFA-3)	
Pounds/in.(min.)	Warp 20 Fill 20

Tensile Strength (CFFA-17)	
Pounds (min.)	Warp 65 Fill 45

Trap Tear Strength (CFFA-16c)	
Pounds	Warp 6 Fill 6

Tack Strength (Stitch) (CFFA-14)	
Pounds (min.)	Warp 51 Fill 42

## Performance Testing: meets or exceeds

Abrasion (CFFA-1a)	
Wyzenbeek, Wire Screen	No change @ 10,000 cycles

Blocking (CFFA-4)	
	No. 1

W-Flex (CFFA-10)	
	Pass

Crock (CFFA-7)	
	Pass

UV (CFFA-2)	
QUV	650 hours

Mildew Resistance - ASTM G-21	
	1 mm Zone of Inhibition

Flame Retardancy	
California Tech. Bulletin 117	Pass
UFAC Fabric, Class 1	Pass

## Miscellaneous

Application	
	Outdoor

Outside Processes	
	Foam Lamination

Finish	
	Clear Vinyl



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • [www.omnova.com](http://www.omnova.com)  
contact us at [upholstery@omnova.com](mailto:upholstery@omnova.com)

BOLTASOFT is a registered trademark of OMNOVA Solutions Inc.  
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA  
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT [WWW.OMNOVA.COM](http://WWW.OMNOVA.COM).  
© 2007 OMNOVA Solutions Inc. 9/07  
QA #: 015-20-180 • 04/13/07 • R: 1