

BoltaSoft® Marine Upholstery

Underlining

Product Specifications:

General	
Total Wt. – oz./sq. yd. (CFFA-700d)	5.6 ± 10%
Total Wt. – oz./lin. yd. (CFFA-700d)	8.4
Width (min.) – in. (CFFA-700a)	54"
Face Content	PVC

Backing	
Construction	Woven
Content	100% Polyester
Fiber Type	Spun

Tensile Strength (CFFA-17)	
Pounds (min.)	Warp 150 Fill 100

Tack Strength (Stitch) (CFFA-14)	
Pounds (min.)	Warp 68 Fill 68

Performance Testing: meets or exceeds

Abrasion (CFFA-1a)	
Wyzenbeek, Wire Screen	Pass - 10,000 cycles

Blocking (CFFA-4)	
	No. 1

W-Flex (CFFA-10)	
	Pass 30,000

Crock (CFFA-7)	
	20 cycles - no stain

UV (CFFA-2)	
QUV	650 hours

Mildew Resistance - ASTM G-21	
	No growth

Miscellaneous

Application	
	Outdoor

Finish	
	Clear Vinyl



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com
 contact us at upholstery@omnova.com

BOLTASOFT is a registered trademark of OMNOVA Solutions Inc.
 ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA
 STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM.
 © 2007 OMNOVA Solutions Inc. 9/07
 QA #: 015-20-141 • 03/31/05 • R: 0