

## SUNCRYL<sup>®</sup> 129 Vinyl Acrylic Copolymer Release Coating

**SUNCRYL 129** release coating offers tight release, and excellent solvent and high temperature resistance, and develops excellent toughness after curing. Designed for hot melt, solvent-based natural rubber or water-based adhesives, **SUNCRYL 129** exhibits excellent mechanical stability and is low foaming, which enhances process efficiency and minimizes downtime.

### FEATURES

- Tight Release
- Excellent Solvent Resistance
- High Temperature Resistance
- May be combined with Release Coatings at 10-30% addition, to tighten up tape overlap properties

### TYPICAL PROPERTIES

pH:	3.0 – 6.0
Solids:	40.0 – 44.0%
Density:	8.6 lbs/gal
Viscosity:	<200 cps RVT/25°C #1 spindle @50 rpm
Tg:	+28°C
Grit:	<20 ppm (200 mesh)

**Comments: OMNOVA Solutions provides many primers and release products designed for the tape and label industry. Because the nature of tape and label products is influenced by the selection of adhesives, application techniques and use expectations, etc., a great variety of coatings has been developed. Please call your OMNOVA Solutions representative to discuss your particular primer or release coating needs.**

### STORAGE AND HANDLING

- Recommended shelf life of 6 months (always test to recertify release force).
- Stir and mix well before using.
- Protect from freezing.
- Refer to Material Safety Data Sheets for additional details.

#### NOTE:

Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, or whether such use will infringe the intellectual property rights of third parties.

