

SECOAT® 163

Writeable, Low Gloss Release Coating

Release surfaces that can be printed with water-based inks and ink-jet inks are especially difficult to provide. **SECOAT 163** coatings achieve a balance of loose to mid-range peel values and excellent ink-jet printing performance. The clear, low-gloss coating performs well in self-wound ink-jet roll labels and other writeable paper tape applications.

FEATURES

- . Aqueous emulsion -- no solvent emissions
- . Easy to apply with roll or knife applicators
- . Sharp, dense ink-jet images
- . Releases from various adhesives

TYPICAL PROPERTIES

Solids:	36.0 – 38.0%
Viscosity:	<400 cps RVT/25°C, #3 spindle @ 100 rpm
pH:	5.0 – 6.5

Comments: OMNOVA Solutions provides many primers and release products designed for the tape and label industry. Because the nature of tape and label products is influenced by the selection of adhesives, application techniques and use expectations, etc., a great variety of coatings has been developed. Please call your OMNOVA Solutions representative to discuss your particular primer or release coating needs.

STORAGE AND HANDLING

- Shelf life of 6 months (always test to recertify release force).
- Stir, mix well before using.
- Protect from freezing.
- Refer to Material Safety Data Sheets for additional details.

NOTE:

Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, or whether such use will infringe the intellectual property rights of third parties.



OMNOVA Solutions Inc. • 1455 J.A. Cochran ByPass • Chester, SC 29706
Telephone • 803-385-5181 • www.omnova.com

SECOAT is a registered trademark of OMNOVA Solutions Inc.

ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM
©2010 OMNOVA Solutions Inc.
March 2010