

SUNCRYL® CH 1100 Paper Tape Release Coating

SUNCRYL CH 1100 high solids release coating is designed for multipurpose creped paper masking tapes and provides easy to moderate release values for solvent-based (toluene) natural rubber, SIS based and/or acrylic water based adhesives.

FEATURES

- Aqueous emulsion (no solvent emissions)
- Clear coating
- Easy to medium release levels
- Low temperature cure, fast drying
- Excellent mechanical stability
- Low foaming
- Excellent water resistance

TYPICAL PROPERTIES

pH:	4 - 6
Solids:	44 - 46%
Density:	8.9 lbs/gal (25°C)
Viscosity:	<200 cps RVT/25°C #2 spindle @ 20rpm

Comments: OMNOVA Solutions provides many release products designed for the tape industry. Because of the unique nature of tape products (adhesive selection, application techniques and use expectations, etc.), a great variety of coatings have been developed. Please call your OMNOVA Solutions representative to discuss your particular tape release coating needs.

STORAGE AND HANDLING

- Shelf life of 6 months. Test to recertify release force.
- Stir, mix well before using.
- Protect from freezing.
- Refer to Material Safety Data Sheets for additional details

NOTE:

Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, or whether such use will infringe the intellectual property rights of third parties.