



SUNCRYL[®] CR 192 Non-Silicone Paper Tape Release Coating

SUNCRYL CR 192 non-silicone release coating was designed for use with water based acrylic pressure sensitive adhesives to offer outstanding high speed unwind properties and excellent stability of release in aged masking tape products. **SUNCRYL CR 192** is intended to offer a looser release than its counterpart - Suncryl CR 191.

FEATURES

- Non-silicone aqueous emulsion (no solvent emissions)
- Clear coating intended for water based acrylic pressure sensitive adhesive masking tapes
- Loose release versus Suncryl CR 191
- Curable for solvent and humidity resistance

TYPICAL PROPERTIES

pH:	7
Solids:	42%
Density:	9.0 lbs/gal (25°C)
Viscosity:	<500 cps RVT/25°C #2 spindle @ 20 rpm

Comments: OMNOVA Solutions provides many release coat products designed for the tape industry. Because of the unique nature of tape products (adhesive selection, application techniques and use expectations, etc.), a wide variety of coatings have been developed. Please call your OMNOVA Solutions representative to discuss your particular tape release coating needs.

STORAGE AND HANDLING

- Recommended shelf life of 6 months; test to recertify release force
- Stir, mix well before using
- Protect from freezing
- Refer to Material Safety Data Sheets for additional details

NOTE:

Although data supplied above are believed to be accurate, each user is advised to make his or her own determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such a use will comply with all applicable laws or regulations, or whether such a use will not infringe the intellectual property rights of third parties.

Revised October 11, 2006

