

SunCryl® SX 3187-104-4 Paper Tape Release Coating

SUNCRYL SX 3187-104-4 release coating is designed for multipurpose creped paper masking tapes. **SUNCRYL SX 3187-104-4** is intended to offer easy release values and excellent water resistance for solvent-based (toluene) natural rubber, SIS based and/or acrylic water based adhesives.

FEATURES

- Aqueous emulsion (no solvent emissions)
- Clear coating
- Easy release levels
- Excellent water resistance
- Excellent mechanical stability
- Low foaming

TYPICAL PROPERTIES

pH:	4.0
Solids:	42 %
Density:	9.0 lbs/gal (@25°C)
Viscosity:	300 cps (RVT/25°C #2 spindle @20rpm)

Comments: OMNOVA Solutions provides many release products designed for the tape industry. Because of the unique nature of tape products (adhesive selection, application techniques and use expectations, etc.), a great variety of coatings have been developed. Please call your OMNOVA Solutions representative to discuss your particular tape release coating needs.

STORAGE AND HANDLING

- Shelf life of 6 months. Test to recertify release force.
- Stir, mix well before using.
- Protect from freezing.
- Refer to Material Safety Data Sheets for additional details.

NOTE:

Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, or whether such use will infringe the intellectual property rights of third parties.