

SUNCRYL® CH 2200 Paper Tape Release Coating

SUNCRYL® CH 2200 release coating is designed for multipurpose creped paper masking tapes. It offers easy-to-moderate release values for both solvent-based (toluene) natural rubber and/or SIS based adhesives.

<u>FEATURES</u>	<u>TYPICAL PROPERTIES</u>
<ul style="list-style-type: none">• Aqueous emulsion	pH: 4.0
<ul style="list-style-type: none">• Less settling, easily dilutable	Solids: 41%
<ul style="list-style-type: none">• Clear coating	Density: 8.9 lbs/gal (25°C)
<ul style="list-style-type: none">• Easy to medium release levels	Viscosity: <500 cps
<ul style="list-style-type: none">• Compatible with Suncryl 3031® and Suncryl® 129 RVT/25°C to provide easier or tighter release properties	#2 spindle @ 20 rpm
<ul style="list-style-type: none">• Curable for solvent and humidity resistance	

Comments: OMNOVA Solutions provides many release products designed for the tape industry. Because of the unique nature of tape products (adhesive selection, application techniques and use expectations, etc.), a great variety of coatings have been developed. Please call your OMNOVA Solutions representative to discuss your particular tape release coating needs.

STORAGE AND HANDLING

- Shelf life of 6 months, test to recertify release force
- Stir, mix well before using
- Protect from freezing
- Refer to Material Safety Data Sheets for additional details

NOTE:
Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product(s) is/are appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, or whether such use will infringe the intellectual property rights of third parties.

Revised June 14, 2007

