

# Boltaflex®

## Antigua

### Product Specifications:

#### General

Total Wt. - oz./sq. yd. (CFFA-700d)	11.0
Total Wt. - oz./lin. yd. (CFFA-700d)	16.5
Width (min.) - in. (CFFA-700a)	54"
Gauge	.039
Face Content	Polyurethane

#### Backing

Construction	Knit
Weight - oz./sq. yd.	5.3
Content	Polyester
Fiber Type	Spun

#### Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0
	Fill 4.0

#### Tensile Strength (CFFA-17)

Pounds (min.)	Warp 80
	Fill 80

#### Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 15
	Fill 15

#### Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 40
	Fill 40

### Performance Testing: meets or exceeds

#### Abrasion

Wyzenbeek, Wire Screen	10,000 cycles
Wyzenbeek, Cotton Duck	200,000 cycles

#### Blocking (CFFA-4)

Pass

#### W-Flex (CFFA-10)

Pass

#### Crock (CFFA-7)

Pass

#### UV (CFFA-2)

QUV	40 hours (indoors)
-----	--------------------

#### Flame Retardancy

California Tech. Bulletin 117	Pass
UFAC Fabric, Class 1	Pass
NFPA 260	Pass

### Miscellaneous:

#### Application

Indoors

#### Finish

Polyurethane



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • [www.omnova.com](http://www.omnova.com)  
contact us at [upholstery@omnova.com](mailto:upholstery@omnova.com)

BOLTAFLEX is a registered trademark of OMNOVA Solutions Inc.  
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA  
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT [WWW.OMNOVA.COM](http://WWW.OMNOVA.COM)  
© 2009 OMNOVA Solutions Inc. QA# 007-CG-004 • 04/09/09