

# Boltaflex®

Cabo

## Product Specifications:

### General

Total Wt. - oz./sq. yd. (CFFA-700d)	11.0
Total Wt. - oz./lin. yd. (CFFA-700d)	16.5
Width (min.) - in. (CFFA-700a)	54"
Gauge	.039
Face Content	Polyurethane

### Backing

Construction	Knit
Weight - oz./sq. yd.	5.3
Content	Polyester
Fiber Type	Spun

### Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0
	Fill 4.0

### Tensile Strength (CFFA-17)

Pounds (min.)	Warp 80
	Fill 80

### Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 15
	Fill 15

### Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 40
	Fill 40

## Performance Testing: meets or exceeds

### Abrasion

Wyzenbeek, Wire Screen	10,000 cycles
Wyzenbeek, Cotton Duck	200,000 cycles

### Blocking (CFFA-4)

Pass

### W-Flex (CFFA-10)

Pass

### Crock (CFFA-7)

Pass

### UV (CFFA-2)

QUV	40 hours (indoors)
-----	--------------------

### Flame Retardancy

California Tech. Bulletin 117	Pass
UFAC Fabric, Class 1	Pass
NFPA 260	Pass

## Miscellaneous:

### Application

Indoors

### Finish

Polyurethane



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • [www.omnova.com](http://www.omnova.com)  
contact us at [upholstery@omnova.com](mailto:upholstery@omnova.com)

BOLTAFLEX is a registered trademark of OMNOVA Solutions Inc.  
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA  
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT [WWW.OMNOVA.COM](http://WWW.OMNOVA.COM)  
© 2009 OMNOVA Solutions Inc. QA# 007-CG-004 • 04/09/09