

Boltaflex®

Serengeti

Product Specifications:

General

Total Wt. - oz./sq. yd. (CFFA-700d)	11.0
Total Wt. - oz./lin. yd. (CFFA-700d)	16.5
Width (min.) - in. (CFFA-700a)	54"
Gauge	.039
Face Content	Polyurethane

Backing

Construction	Knit
Weight - oz./sq. yd.	5.3
Content	Polyester
Fiber Type	Spun

Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0
	Fill 4.0

Tensile Strength (CFFA-17)

Pounds (min.)	Warp 80
	Fill 80

Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 15
	Fill 15

Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 40
	Fill 40

Performance Testing: meets or exceeds

Abrasion

Wyzenbeek, Wire Screen	10,000 cycles
Wyzenbeek, Cotton Duck	200,000 cycles

Blocking (CFFA-4)

Pass

W-Flex (CFFA-10)

Pass

Crock (CFFA-7)

Pass

UV (CFFA-2)

QUV	40 hours (indoors)
-----	--------------------

Flame Retardancy

California Tech. Bulletin 117	Pass
UFAC Fabric, Class 1	Pass
NFPA 260	Pass

Miscellaneous:

Application

Indoors

Finish

Polyurethane



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com
contact us at upholstery@omnova.com

BOLTAFLEX is a registered trademark of OMNOVA Solutions Inc.
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM
© 2009 OMNOVA Solutions Inc. QA# 007-CG-004 • 04/09/09