

# Boltaflex<sup>®</sup> Contract Upholstery

Palermo

## Product Specifications:

### General

Total Wt. - oz./sq. yd. (CFFA-700d)	14.0 ± 10%
Total Wt. - oz./lin. yd. (CFFA-700d)	21
Width (min.) - in. (CFFA-700a)	54"
Face Content	Urethane/PVC foam base

### Backing

Construction	Sheeting
Weight - oz./sq. yd.	3.5
Content	Polyester/cotton
Fiber Type	Staple

### Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0
	Fill 4.0

### Tensile Strength (CFFA-17)

Pounds (min.)	Warp 85
	Fill 90

### Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 15
	Fill 15

### Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 65
	Fill 65

## Performance Testing: meets or exceeds

### Abrasion

Wyzenbeek, Wire Screen	30,000 cycles
Wyzenbeek, Cotton Duck	50,000 cycles

### Blocking (CFFA-4)

No. 1

### W-Flex (CFFA-10)

25,000 cycles

### Crock (CFFA-7)

20 cycles - no stain

### UV (CFFA-2)

QUV 40 hours (indoor)

### Flame Retardancy

California Tech. Bulletin 117	Pass
NFPA 260	Pass
UFAC Fabric, Class 1	Pass

## Miscellaneous:

### Application

Indoor

### Finish

Urethane



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • [www.omnova.com](http://www.omnova.com)  
contact us at [upholstery@omnova.com](mailto:upholstery@omnova.com)

BOLTAFLEX and PREFIX are registered trademarks of OMNOVA Solutions Inc.  
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA  
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT [WWW.OMNOVA.COM](http://WWW.OMNOVA.COM)  
© 2011 OMNOVA Solutions Inc. QA#007-CG-003 Rev.3 • 11/01/10