

Boltaflex®

Varsity

Product Specifications:

General

Total Wt. - oz./sq. yd. (CFFA-700d)	20.1
Total Wt. - oz./lin. yd. (CFFA-700d)	30.0
Width (min.) - in. (CFFA-700a)	54"
Face Content	Vinyl

Backing

Construction	Non-woven
Weight - oz./sq. yd.	3.5
Content	Polyester
Fiber Type	Staple

Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 6.0
	Fill 6.0

Tensile Strength (CFFA-17)

Pounds (min.)	Warp 81
	Fill 81

Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 43
	Fill 36

Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 53
	Fill 47

Performance Testing: meets or exceeds

Abrasion

Wyzenbeek, Wire Screen	25,000 cycles
------------------------	---------------

Blocking (CFFA-4)

Pass

W-Flex (CFFA-10)

Pass

Crock (CFFA-7)

Pass

UV (CFFA-2)

QUV	40 hours (indoors)
-----	--------------------

Flame Retardancy

California Tech. Bulletin 117	Pass
UFAC Fabric, Class 1	Pass

Miscellaneous:

Application

Indoors

Finish

Dry cleanable polyurethane



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com
contact us at upholstery@omnova.com

BOLTAFLEX is a registered trademark of OMNOVA Solutions Inc.
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM
© 2010 OMNOVA Solutions Inc. QA# 033-17-022 • 11/08/07 • Rev.1