

Features:

- Eco-preferred construction
 - Does not contain PVC or plasticizers
 - Complies with Section 108: Phthalates of the Consumer Product Safety Improvement Act (CPSIA)
 - Formulated to comply with RoHS (2002/95) directive and E.U. REACH (18 June 2010) chemicals regulation
- Polyurethane face, polyester knit backing
- Bleach safe for disinfection - www.omnova.com/pinnacle/bleach

Product Specifications:

General

Total Wt. - oz./sq. yd. (CFFA-700d)	13 ± 10%
Total Wt. - oz./lin. yd. (CFFA-700d)	19.5 ± 10%
Width (min.) - in. (CFFA-700a)	54"
Gauge	.039
Face Content	Polyurethane

Backing

Construction	Knit
Weight - oz./sq. yd.	5.3
Content	Polyester
Fiber Type	Spun

Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0 / Fill 4.0
----------------------	---------------------

Tensile Strength (CFFA-17)

Pounds (min.)	Warp 80 / Fill 80
---------------	-------------------

Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 15 / Fill 15
---------------	-------------------

Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 40 / Fill 40
---------------	-------------------

Performance Testing: meets or exceeds

Abrasion (CFFA-1a)

Wyzenbeek, wire screen	10,000 cycles
Wyzenbeek, #8 cotton duck	200,000 cycles

Blocking (CFFA-4)

Pass

W-Flex (CFFA-10)

Pass

Crock (CFFA-7)

Class 5 wet / Class 5 dry

UV (CFFA-2)

QUV	400 hours (indoor)
-----	--------------------

Cold Crack (CFFA-6a)

Roller temperature	-20° F
--------------------	--------

Flame Retardancy

California Technical Bulletin 117, Section E	Pass
UFAC Fabric, Class 1	Pass
FAR 25.853A	Pass
FMVSS-302	Pass
NY/NJ Port of Authority	Pass
BIFMA	Pass
NFPA 260	Pass

Applications:

Indoor

