

## Features:

- Eco-preferred construction
  - Does not contain PVC or plasticizers
  - Complies with Section 108: Phthalates of the Consumer Product Safety Improvement Act (CPSIA)
- Polyurethane face, rayon backing
- Bleach safe for disinfection - [www.omnova.com/pinnacle/bleach](http://www.omnova.com/pinnacle/bleach)

## Product Specifications:

### General

Total Wt. - oz./sq. yd. (CFFA-700d)	13 ± 10%
Total Wt. - oz./lin. yd. (CFFA-700d)	19.5 ± 10%
Width (min.) - in. (CFFA-700a)	54"
Gauge	.045
Face Content	Polyurethane

### Backing

Construction	Brushed woven
Weight - oz./sq. yd.	4.0
Content	Rayon
Fiber Type	Spun

### Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0 / Fill 4.0
----------------------	---------------------

### Tensile Strength (CFFA-17)

Pounds (min.)	Warp 70 / Fill 70
---------------	-------------------

### Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 10 / Fill 10
---------------	-------------------

### Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 50 / Fill 50
---------------	-------------------

## Performance Testing: meets or exceeds

### Abrasion (CFFA-1a)

Wyzenbeek, wire screen	30,000 cycles
Wyzenbeek, #8 cotton duck	200,000 cycles

### Blocking (CFFA-4)

Pass

### W-Flex (CFFA-10)

Pass

### Crock (CFFA-7)

Class 5 wet / Class 5 dry

### UV (CFFA-2)

QUV	40 hours (indoor)
-----	-------------------

### Cold Crack (CFFA-6a)

Roller temperature	-20° F
--------------------	--------

### Flame Retardancy

California Technical Bulletin 117, Section E	Pass
UFAC Fabric, Class I	Pass
FMVSS-302	Pass
NFPA 260	Pass

## Applications:

### Indoor

