



City Grey  
532623



Porcelain  
514656




Buttercup  
514710



Cardinal  
514978



Sediment  
532620




Snow Cap  
515206



Soft Jade  
532624



Dijon  
520057



Stoneware  
515039



Honey  
520966



Blaze  
514976



Pebble  
532621



Wedgewood  
518436



Morning Dew  
515419



Limon  
532625



Quarry  
517418



River Clay  
514695



Hibiscus  
518435



Plum Dusk  
514983



Bluette  
515176



Pale Aqua  
515558



Chervil  
514804



Maize  
519926



Seville  
514711



Flamenco  
520007



Violet  
514985



Blue Moon  
514977



Glacier  
514980



Keylime  
514982



Sandstone  
518434



Blood Orange  
532626



Pomegranate  
514940



Wisteria  
515033



Azure  
514728



Juniper  
514706



Aloe  
514600



Portobello  
515150



Nutmeg  
514732



Empire  
515009



Rain  
514984



Cobalt  
532627



Fern  
514975



Kelp  
514981



Doe  
514712



Coral Reef  
514979



Maroon  
515390



Steely  
532622



Paradise  
520242



Sprite  
514866



Sequoia  
519038



Grounded  
517904



Sienna  
517419



Rioja  
514694



Shale  
515052



Huron  
514666



Keystone  
515177



Licorice  
514681

Content	100% PVC face, polyester terry loop knit backing
Finish	<b>PreFixx</b> <sup>®</sup> protective finish for increased stain resistance and easy cleaning. Bleach cleanable and may be disinfected with a variety of hospital grade disinfectants without discoloring or damaging the finish. Disinfection does not replace the need for regular care and maintenance.
Width	54 in. [137 cm]
Weight	28 oz/lin. yd. [18.7 oz/yd <sup>2</sup> ] / 849 g/lin. m [619 g/m <sup>2</sup> ]
Performance Requirements	Meets or exceeds ACT <sup>®</sup> Performance Guidelines



Also meets or exceeds:

- CFFA-1a Wyzenbeek - 1.3 million double rubs (cotton duck abradant)
- Fungal resistance ASTM G-21-13
- Bacterial resistance AATCC 147-2011 & AATCC 100-2004
- Oil resistance CFFA-13
- Surface resistance AATCC-76 Antistatic
- Urine resistance AATCC-6 Colorfastness to Acids and Alkali
- Resistance to sulfide stain ASTM D 1712
- ASTM E-84 Adhered to GRC, Class 1 or A
- BIFMA, Class A
- Boston Fire Dept. IX-1
- California Technical Bulletin 117-2013, Section 1
- FAR 25.853a & Appendix F Part 1 (a)(1)(ii)
- Federal Specification CID A-A-2950A
- FMVSS-302
- IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette
- IMO Part 8 Upholstered Furniture 3.2 Propane Flame
- NFPA 701 Small Scale
- NFPA 260, Class 1
- NY/NJ Port Authority
- UFAC Fabric, Class 1

Applications	Indoor/Outdoor	
	<ul style="list-style-type: none"> <li>• Corporate Office</li> <li>• Healthcare</li> <li>• Recreational Vehicles</li> </ul>	<ul style="list-style-type: none"> <li>• Food Service</li> <li>• Hospitality and Entertainment</li> <li>• Retail</li> </ul>

*Though our upholstery can be used in many applications, customers are responsible for selecting an upholstery with attributes that meet the requirements of the specific end-use application – not all upholstery is suitable for all applications.*

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.*

For additional cleaning instructions and detailed specification information, visit: [www.omnova.com](http://www.omnova.com)



**World Headquarters**  
25435 Harvard Road  
Beachwood, OH 44122  
United States  
PHONE +1 216 682-7000  
FAX +1 216 453-0104