

Boltaflex upholstery products are well known for their hard-working and long-lasting performance in a wide range of interior environments. Much of this reputation can be attributed to the best-selling *ColorGuard* design.

ColorGuard features a durable, 36 oz. vinyl construction that is resistant to microbial and bacterial attack. Featuring the industry-leading **PreFlxx** protective finish, it has been engineered to be cleaned and disinfected with a wide variety of chemical cleaners without worrying about discoloration or damage to the upholstery finish when the recommended cleaning process is followed.

Industries & Markets

- Corporate Office
- Food Service
- Healthcare
- Hospitality & Entertainment
- Retail
- Recreational Vehicles

End-Use Applications

- Contract Seating
- Dining Seating
- Medical Furnishings
- Guest room furnishings
- Lobby furnishings & millwork
- Spas & Health Clubs
- Theater Seating
- Retail Seating
- Interior Surfaces

Physical Specifications

Weight (CFFA-700d)	36 oz/lin yd [24 oz/yd ²]
Weight, Metric (CFFA-700d)	1,021 g/lin m [680 g/m ²]
Width (CFFA-700a)	54 in. [137 cm]
Face Composition	PVC
Backing Description	Polyester Jersey Knit
Roll Size	30 lin yd [27 lin m]
Emboss Level	Medium
Shipping Weight/ Roll	76 lb [34 kg]

Flame, Smoke & Toxicity

Meets or exceeds the following:

- BIFMA - Class A
- Boston Fire Dept IX 1
- Cal Tech 117-2013 Sec 1
- FAR 25.853a & Appx F Part 1 (a)(1)(ii)
- FMVSS-302
- IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette
- IMO Part 8 Upholstered Furniture 3.2 Propane Flame
- NFPA 260 Class 1
- NFPA 701 Small Scale
- Port Authority of NY/NJ
- UFAC Fabric, Class 1
- Federal Spec CID A-A-2950-A
- ASTM E-84

Performance Features

Protective Finish	PreFixx
Use	Indoor/Outdoor
QUV hours (minimum)	650
Adhesion #/in., min (CFFA-3)	3 Warp, 3 Fill
Tensile Strength #, min (CFFA-17)	110 Warp, 85 Fill
Tack Strength #, min (CFFA-14)	60 Warp, 30 Fill
Trap Tear Strength #, min (CFFA-16c)	25 Warp, 25 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,300,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Biocompatibility Certified ISO 10993-13	Pass
Fungal Resistance (ASTM-G-21)	Pass
Bacterial Resistance (AATCC 147)	Pass
Bacterial Resistance (AATCC 100)	Pass
Cold Crack (CFFA-6a)	-20 °F [-29 °C]
Compatible with Disinfectants	Yes. See Chem Resistance Tech Bulletin for more information.
Bleach-Safe	Yes, 10% Bleach Solution
Resistance to Sulfide Stain (ASTM D1712)	Yes
Oil Resistance (CFFA-13)	Yes

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.



World Headquarters

OMNOVA Solutions Inc.
25435 Harvard Road
Beachwood, OH 44122-6201
USA
Phone: +1 216-682-7000
Email: upholstery@omnova.com

Thailand Manufacturing Plant

111/7 Moo 2, T. Nikompattana
Amphur Nikompattana
Rayong 21180, Thailand
Phone: +011-66-38-897103
Fax: +011-66-38-637749

**OMNOVA Decorative Products
(Shanghai) Co., Ltd**

Manufacturing and China
Headquarters
No. 469 Wenjin Road
Minhang District
Shanghai 200245, China
Phone: +011 (86-21) 6430-7800
Fax: +011 (86-21) 6430-6468

All OMNOVA products and services are offered and sold subject to the OMNOVA standard terms and conditions of sale agreement set forth at www.omnova.com

Trademarks are property of OMNOVA Solutions Inc. unless otherwise noted.

©2019 OMNOVA Solutions Inc.