

Weave NFR is a **Boltaflex** vinyl performance fabric featuring our industry-leading **PreFlxx** protective finish. Formulated without phthalates and fire retardants (FR), **Boltaflex Weave NFR** supports the growing trend towards eco-friendly solutions in contract design.

Industries & Markets

- Corporate Office
- Food Service
- Healthcare
- Hospitality & Entertainment

End-Use Applications

- Office Furniture
- Contract Seating
- Dining Seating
- Medical Furnishings
- Guest room furnishings
- Lobby furnishings & millwork
- Theater Seating
- Spas & Health Clubs

Physical Specifications

Weight (CFFA-700d)	28 oz/lin yd [18.7 oz/yd ²]
Weight, Metric (CFFA-700d)	849 g/lin m [619 g/m ²]
Width (CFFA-700a)	54 in. [137 cm]
Face Composition	PVC
Backing Description	Polyester Terry Loop Knit
Roll Size	40 lin yd [37 lin m]
Emboss Level	Medium
Shipping Weight/ Roll	68 lb [31 kg]

Flame, Smoke & Toxicity

Meets or exceeds the following:

- Cal AB 2998
- BIFMA - Class A
- Cal Tech 117-2013 Sec 1
- NFPA 260 Class 1
- UFAC Fabric, Class 1
- IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette
- IMO Part 8 Upholstered Furniture 3.2 Propane Flame

Performance Features

Protective Finish	PreFixx
Use	Indoor/Outdoor
QUV hours (minimum)	650
Adhesion #/in., min (CFFA-3)	4 Warp, 4 Fill
Tensile Strength #, min (CFFA-17)	85 Warp, 75 Fill
Tack Strength #, min (CFFA-14)	35 Warp, 30 Fill
Trap Tear Strength #, min (CFFA-16c)	20 Warp, 27 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,300,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Fungal Resistance (ASTM-G-21)	Pass
Bacterial Resistance (AATCC 147)	Pass
Bacterial Resistance (AATCC 100)	Pass
Cold Crack (CFFA-6a)	-20 °F [-29 °C]
Slit Tear Resistance (ASTM D2212-00)	Pass
Puncture Resistance (ASTM D4833-07)	Pass
Compatible with Disinfectants	Yes. See Chem Resistance Tech Bulletin for more information.
Bleach-Safe	Yes, 10% Bleach Solution
Surface Resistance - anti-static (AATCC-76)	Yes
Resistance to Sulfide Stain (ASTM D1712)	Yes
Oil Resistance (CFFA-13)	Yes
Urine Resistance (AATCC-6)	Yes

Revision Date: 20-Aug-20

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.



North American Headquarters
 OMNOVA Solutions Inc.
 25435 Harvard Road
 Beachwood, OH 44122-6201
 USA
 Phone: +1 216-682-7000
 Email: upholstery@omnova.com

Thailand Manufacturing Plant
 111/7 Moo 2, T. Nikompattana
 Amphur Nikompattana
 Rayong 21180, Thailand
 Phone: +011-66-38-897103
 Fax: +011-66-38-637749

All OMNOVA products and services are offered and sold subject to the OMNOVA standard terms and conditions of sale agreement set forth at www.omnova.com

Trademarks are property of OMNOVA Solutions Inc. unless otherwise noted.

© OMNOVA Solutions

OMNOVA Solutions Inc., a Synthomer company.