

Verde is a **Boltaflex Ethos** vinyl upholstery from OMNOVA Solutions featuring our industry-leading **PreFixx** protective coating. Formulated without phthalates, fire retardants (FR), and antimicrobial (MR) additives, **Boltaflex Ethos** upholsteries support the growing trend towards eco-friendly solutions in contract design. *Verde* features a leather appearance in a palette of on-trend colors perfect for office, hospitality, and healthcare settings. **Boltaflex Ethos** upholsteries are formulated with only those ingredients needed to provide durability, performance, and comfort.

Industries & Markets

- Corporate Office
- Food Service
- Healthcare
- Hospitality & Entertainment
- Retail

End-Use Applications

- Contract Seating
- Dining Seating
- Medical Furnishings
- Guest room furnishings
- Lobby furnishings & millwork
- Spas & Health Clubs
- Theater Seating
- Retail Seating

Physical Specifications

| | |
|----------------------------|---|
| Weight (CFFA-700d) | 28 oz/lin yd [18.7 oz/yd ²] |
| Weight, Metric (CFFA-700d) | 849 g/lin m [619 g/m ²] |
| Width (CFFA-700a) | 54 in. [137 cm] |
| Face Composition | PVC |
| Backing Description | Polyester Terry Loop Knit |
| Roll Size | 40 lin yd [37 lin m] |
| Emboss Level | Light |
| Shipping Weight/ Roll | 68 lb [31 kg] |

Flame, Smoke & Toxicity

| | |
|---------------------------------|--|
| Meets or exceeds the following: | <ul style="list-style-type: none">• BIFMA - Class A• Cal Tech 117-2013 Sec 1• NFPA 260, Class 1• UFAC Fabric, Class 1• AB 2998• IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette |
|---------------------------------|--|

Performance Features

| | |
|---|--|
| Protective Finish | PreFixx |
| Use | Indoor |
| Adhesion #/in., min (CFFA-3) | 4 Warp, 4 Fill |
| Tensile Strength #, min (CFFA-17) | 85 Warp, 75 Fill |
| Tack Strength #, min (CFFA-14) | 35 Warp, 30 Fill |
| Trap Tear Strength #, min (CFFA-16c) | 20 Warp, 27 Fill |
| Wyzenbeek Abrasion (CFFA-1a) | 1,300,000 Cotton Duck (double rubs) |
| Blocking (CFFA-4 No. 1) | Pass |
| W-Flex - 25,000 cycles (CFFA-10) | Pass |
| Crocking Resistance - 20 cycles no stain (CFFA-7) | Pass |
| Cold Crack (CFFA-6a) | -20 °F [-29 °C] |
| Compatible with Disinfectants | Yes. See Chem Resistance Tech Bulletin for more information. |
| Bleach-Safe | Yes, 10% Bleach Solution |
| Resistance to Sulfide Stain (ASTM D1712) | Yes |
| Oil Resistance (CFFA-13) | Yes |
| Urine Resistance (AATCC-6) | Yes |

Revision Date: 15-August-22

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.



North American Headquarters
OMNOVA Solutions Inc.
25435 Harvard Road
Beachwood, OH 44122-6201
USA
Phone: +1 216-682-7000
Email: upholstery@omnova.com

Thailand Manufacturing Plant
111/7 Moo 2, T. Nikompattana
Amphur Nikompattana
Rayong 21180, Thailand
Phone: +011-66-38-897103
Fax: +011-66-38-637749

All OMNOVA products and services are offered and sold subject to the OMNOVA standard terms and conditions of sale agreement set forth at www.omnova.com

Trademarks are property of OMNOVA Solutions Inc. unless otherwise noted.

©2022 OMNOVA Solutions

OMNOVA A Division of SURTECO.