

Nautolex flooring has the appearance of outdoor carpeting, but has the strength and skid resistance needed for marine environments. It can be used on interior and exterior boat floors, holding up to many years of use. It is available in a variety of colors to coordinate with any design.

Nautolex flooring is specifically designed to be easily cleaned and resist damage from gasoline, oil, alcohol, heat and harsh weather.

### **Industries & Markets**

Marine

### **End-Use Applications**

Coated Fabrics for Boats and Personal Watercraft

# **Physical Specifications**

Weight (CFFA-700d)	50 oz/lin yd [24.3 oz/yd²]	
Weight, Metric (CFFA-700d)	1,417 g/lin m [689 g/m²]	
Width (CFFA-700a)	74 in. [188 cm]	
Face Composition	PVC	
Backing Description	Polyester Woven	
Roll Size	25 lin yd [23 lin m]	
Emboss Level	Heavy	
Shipping Weight/ Roll	85 lb [39 kg]	

## Flame, Smoke & Toxicity

Meets or exceeds the following:	•	Cal Tech 117-2013 Sec 1
		UFAC Fabric, Class 1
	•	IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette
		IMO Part 8 Upholstered Furniture 3.2 Propane Flame

### Performance Features

Protective Finish	Clear Vinyl
Use	Indoor/Outdoor
QUV hours (minimum)	650
Adhesion #/in., min (CFFA-3)	3.5 Warp, 3.5 Fill
Tensile Strength #, min (CFFA-17)	130.5 Warp, 95.5 Fill
Tack Strength #, min (CFFA-14)	81.2 Warp, 70.8 Fill
Trap Tear Strength #, min (CFFA-16c)	15 Warp, 11.9 Fill
Wyzenbeek Abrasion (CFFA-1a)	50,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Fungal Resistance (ASTM-G-21)	Pass

Revision Date: 15-August-22

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.



North American Headquarters

OMNOVA Solutions Inc. 25435 Harvard Road Beachwood, OH 44122-6201 USA

Phone: +1 216-682-7000 Email: upholstery@omnova.com Thailand Manufacturing Plant

111/7 Moo 2, T. Nikompattana Amphur Nikompattana Rayong 21180, Thailand Phone: +011-66-38-897103 Fax: +011-66-38-637749

All OMNOVA products and services are offered and sold subject to the OMNOVA standard terms and conditions of sale agreement set forth at www.omnova.com